

KWVE35-B-S

Recirculating ball bearing carriage

Carriages KWVE..-B-S, narrow carriage, four-row

Teknik bilgiler



Main Dimensions & Performance Data

H	48 mm	height system
B	70 mm	width carriage
L	112 mm	overall length carriage
C	38.000 N	dynamic load rating
C_0	72.000 N	static load rating
M_{0x}	1.465 Nm	static moment rating about X axis
M_{0y}	1.020 Nm	static moment rating about Y axis
M_{0z}	1.020 Nm	static moment rating about Z axis
≈m	1,3 kg	Ağırlık

Veri tablosu, seçilen ürünün boyutları ve temel yük kapasitesi hakkında yalnızca genel bir bakış sunar. Lütfen bu ürüne dair ayrıntılı bilgileri ve kılavuzları inceleyin. Daha ayrıntılı bilgi için internet sitemizdeki iletişim formunu kullanabilirsiniz.









Mounting dimensions

A_1	18 mm	Distance from locating edge on carriage to locating edge on guideway
J_B	50 mm	
b	34 mm	width rail
A_2	10 mm	Distance from locating edge to hole
L_1	80 mm	
L_S	1,65 mm	
J_L	50 mm	
H_1	6,7 mm	Free space, system dimension
H_5	6,75 mm	
T_5	13,5 mm	Thread depth
G_2	M8	fixing screws above (DIN ISO 4762-12.9)
G2 M_A	41 Nm	maximum tightening torque
A_3	12,3 mm	position lubrication connector
G_3	M6	lubrication connector
t G_3	7 mm	maximum permissible screw depth for lubrication connectors
A_4	11 mm	position lubrication connector
G_4	M6	lubrication connector
t G_4	7 mm	maximum permissible screw depth for lubrication connectors
J_{L6}	22 mm	position lubrication connector

Additional information

VMKB_065	KWVE	Material name

Veri tablosu, seçilen ürünün boyutları ve temel yük kapasitesi hakkında yalnızca genel bir bakış sunar. Lütfen bu ürüne dair ayrıntılı bilgileri ve kılavuzları inceleyin. Daha ayrıntılı bilgi için internet sitemizdeki iletişim formunu kullanabilirsiniz.



S05

Veri tablosu, seçilen ürünün boyutları ve temel yük kapasitesi hakkında yalnızca genel bir bakış sunar. Lütfen bu ürüne dair ayrıntılı bilgileri ve kılavuzları inceleyin. Daha ayrıntılı bilgi için internet sitemizdeki iletişim formunu kullanabilirsiniz.