


VSA200414-N [↗](#)

Slewing ring, four Point contact bearings, external gear

Slewing ring, four Point contact bearings,
external gear

Teknik bilgiler



Main Dimensions & Performance Data

d_i	342 mm	Bore Diameter
	0,5 mm	Bore diameter upper tolerance
	0 mm	Bore diameter lower tolerance
H	56 mm	Height
D_a	503,3 mm	Outside Diameter
h_a	44,5 mm	Width outer ring
h_i	44,5 mm	height of inner ring
$\approx m$	31,3 kg	Ağırlık



Dimensions

D_i	415,5 mm	Inner diameter outer ring
	0,5 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
d_a	412,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,5 mm	Outside diameter inner ring lower tolerance
n_i	24	Number of fixing holes in inner ring
L_i	368 mm	Pitchcircle diameter fixing holes inner ring
d_B	14 mm	Fixing bore
n_a	20	Number of fixing holes in outer ring
L_a	455 mm	Pitchcircle diameter fixing holes outer ring
d_{Ba}	M12	Tread fixing bore
G_l	20 mm	Thread depth fixing hole
$F_{r\text{zul}}$	82.600 N	Max. radial load fixing screws (friction locking)
d_0	495 mm	Pitch circle diameter gearing
m	5 mm	Modul of gearing
z	99	Number of teeth
	-0,17 mm	Profile shift
b	40 mm	Width gearing
D	480 mm	Offset diameter outer ring
	0 mm	Offset diameter outer ring upper tolerance
	-0,5 mm	Offset diameter outer ring lower tolerance
$F_{z\text{norm}}$	15.900 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
$F_{z\text{max}}$	23.600 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)

Temperature range

T_{min}	-25 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.

Calculation factors

C_a	137.000 N	Basic dynamic load rating, axial
C_{0a}	660.000 N	Basic static load rating, axial
C_r	124.000 N	Basic dynamic load rating, radial
C_{0r}	305.000 N	Basic static load rating, radial