
**VSI200744-N**

Slewing ring, Four Point contact bearing, internal gear teeth

Slewing ring, Four Point contact bearing,  
internal gear teeth

## Teknik bilgiler

**Main Dimensions & Performance Data**

$d_1$	648 mm	Bore Diameter
T	4,5 mm	Length centering inner ring
H	56 mm	Height
$D_a$	816 mm	Outside Diameter
	-0,6 mm	Outside diameter lower tolerance
	0 mm	Outside diameter upper tolerance
$h_a$	44,5 mm	Width outer ring
$h_i$	44,5 mm	Width inner ring
$\approx m$	58,3 kg	Ağırlık



### Dimensions

$D_i$	745,5 mm	Inner diameter outer ring
	0,6 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
$L_a$	790 mm	Pitchcircle diameter fixing holes outer ring
$n_a$	40	Number of fixing holes in outer ring
$d_B$	14 mm	Fixing bore
$d_a$	742,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,6 mm	Outside diameter inner ring lower tolerance
$L_i$	705 mm	Pitchcircle diameter fixing holes inner ring
$d_{Bi}$	M12	Tread fixing bore
$G_I$	20 mm	Thread depth fixing hole
$n_i$	40	Number of fixing holes in inner ring
$F_{r\text{zul}}$	165.200 N	Max. radial load fixing screws (friction locking)
$m$	6 mm	Modul of gearing
$z$	110	Number of teeth
$d_0$	660 mm	Pitch circle diameter gearing
$F_{z\text{norm}}$	23.700 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
$F_{z\text{max}}$	35.000 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)

### Temperature range

$T_{\text{min}}$	-25 °C	Operating temperature min.
$T_{\text{max}}$	80 °C	Operating temperature max.

### Calculation factors

$C_a$	171.000 N	Basic dynamic load rating, axial
$C_{0a}$	1.200.000 N	Basic static load rating, axial
$C_r$	155.000 N	Basic dynamic load rating, radial
$C_{0r}$	550.000 N	Basic static load rating, radial